

AUTHOR INDEX

- Abdul-Karim, M. A. H., 405
 Balossier, G., 1
 Bataillard, P., 245
 Bergveld, P., 463
 Betz, R., 207
 Beumer, K. E., 193
 Bieth, C., 291
 Birkholz, U., 179
 Bonnet, N., 1
 Boucher, H., 291
 Bychkov, E. A., 275
 Byung-Ki Sohn, 441

 Clark, A. E., 323
 Clechet, P., 245
 Collins, R. A., 389
 Cox, D. F., 101
 Crary, S. B., 303
 Cunningham, M. J., 225

 Dario, P., 35
 de Jong, L. P., 193
 Delapierre, G., 291
 den Braber, G. P., 193
 Dobos, K., 333
 Dong-Sung Ma, 441
 Drabowitch, S., 313
 Duk-Dong Lee, 441

 Femi, D., 35
 Fettig, R., 179

 Gabriel, K. J., 341
 Galiatsatos, C., 455
 Gerliczy, G., 207
 Grange, H., 291
 Grattan, K. T. V., 375
 Gutierrez Monreal, F. J., 129

 Habibzadeh, A., 367
 Heber, K. V., 145

 Heineman, W. R., 455
 Hisamoto, J., 415
 Hötzel, G., 449
 Huang Jin-Biao, 9

 Ikariyama, Y., 455

 Jaffrezic-Renault, N., 245
 Janata, J., 121
 Jones, B. E., 225
 Jung, H.-J., 285

 Kang, W. P., 349
 Koestoer, R. A., 91
 Kong, X. G., 245
 Kuwata, S., 415

 Lalevic, B., 349
 Lambrechts, M., 185
 Leaver, P., 225
 Legras, J. C., 235
 Lundström, I., 255

 Mari, C. M., 129
 Martelet, C., 245
 Mehregany, M., 341
 Minhang Bao, 49
 Miura, N., 415
 Mokwa, W., 333
 Morrison, S. Roy, 425

 Nordholt, E. H., 193

 Ovenston, A., 159

 Palmer, A. W., 375
 Paszczynski, S., 57
 Pistre, J. D., 313
 Poteat, T. L., 349
 Priel, M., 235
 Puers, B., 57

 Rahnavard, M. H., 367
 Ranson, C., 235
 Rosenzweig, J., 179

 Sansen, W., 57, 185
 Savage, H. T., 323
 Semancik, S., 101
 Shaw, J. E. A., 297
 Sibbald, A., 297
 Silard, A. P., 23
 Simov, S., 1
 Simova, E., 1
 Steyaert, M., 185
 Stoev, I., 1

 Taha, S. M. R., 405
 Tong Qin-Yi, 9
 Trimmer, W. S. N., 341

 van der Schoot, B. H., 463
 Vivaldi, F., 35
 Vlasov, Yu. G., 275
 Voorthuijzen, J. A., 463

 Walls, J. R., 159
 Weppner, W., 107, 449
 Wilson, A., 389
 Winqvist, F., 255
 Wun-Fogle, M., 323

 Xu, J. F., 349

 Yamauchi, S., 455
 Yamazoe, N., 415
 Yannopoulos, L. N., 77, 263
 Yan Wang, 49
 Yoo, K.-S., 285

 Zardini, Ch., 313
 Zimmer, G., 333

SUBJECT INDEX

- Analysis
 - and design of four-terminal Si pressure sensor at centre of diaphragm, 49
- Anionic substances
 - polypyrrole electrode as detector of, 455
- Antimony
 - Sb-doped stannic oxide-based thick-film gas sensors, 77
- Arsine detection
 - Pd-gate MOS devices for, 333
- Automatic testing equipment
 - application of multiple regression methods and, to characterization of 'smart' sensors, 235
- Carbon monoxide
 - gas sensors, low power thick film, 441
- Catalysts
 - commercial supported Ni, d.c. conductivity used as sensor for high-temperature H₂ chemisorption on, 159
- Chalcogenide glasses
 - electrochemical ion-selective sensors based on, 275
- CHEMFET
 - selective gates, preparation of, by thin silica layer grafting and their behaviour, 245
- Chemical selectivity
 - of field-effect transistors, 121
- Chemical sensors
 - use of polymer materials as sensitive elements in physical and, 129
- CMOS flow sensor
 - with constant chip temperature (CCT) operation, novel, 9
- Constant chip temperature (CTT)
 - novel CMOS flow sensor with, operation, 9
- D.c. conductivity
 - uses as sensor for high-temperature H₂ chemisorption on commercial supported Ni catalysts, 159
- Density analysis
 - noise power spectrum, of planar Ag/AgCl electrodes, 185
- Electrical analogy
 - study of thermal fields of zero-method heat flux sensor by, 91
- Electrical characteristics
 - of planar phthalocyanine thin film gas sensors, 389
- Electrochemical gas sensors
 - solid-state, 107
- Electrochemical ion-selective sensors
 - based on chalcogenide glasses, 275
- Electrode(s)
 - Ag/AlCl, noise power spectrum density analysis of, 185
 - polypyrrole, as detector of anionic substances, 455
- Electrolytes
 - potentiometric gas sensors based on fast solid, 449
- Electro-optical performance
 - of large-area Si sensors for radiative energy signals, 23
- Fiber-optic catheter-tip sensor
 - based on photoelastic effect, 35
- Field-effect transistors
 - chemical selectivity of, 121
- Flow meter
 - floating-ball, extremely low-power bipolar integrated impedance-variation detector for use in, 193
- Flow sensor
 - novel CMOS, with constant chip temperature (CCT) operation, 9
- Fluorescent materials
 - fibre-optic-addressed temperature transducers using solid-state, 375
- Force (pressure) sensor
 - thick-film fabrication methods for, assessment of, 57
- Gas-dosed tin oxide
 - fundamental characterization of clean and, 101
- Gas-sensing characteristics
 - of semiconducting materials based on In₂O₃ depending on composition changes, 285
- Gas sensor(s)
 - CO, low power thick film, 441

- p-type semiconductor thick film, 263
 - planar phthalocyanine thin film, electrical characteristics of, 389
 - potentiometric, based on fast solid electrolytes, 449
 - Sb-doped stannic oxide-based thick-film, 77
 - semiconductor, selectivity in, 425
 - solid-state electrochemical, 107
- Heat flux sensor
- zero-method, study of thermal fields of, by electrical analogy, 91
- High temperature(s)
- H₂ chemisorption, d.c. conductivity used as sensor for, on commercial supported Ni catalysts, 159
 - humidity measurement at, 145
- Humidity measurement
- at high temperatures, 145
- Humidity sensor
- capacitive, with very fast response time and very low hysteresis, 291
- Hydrocarbons
- thin metal film-oxide-semiconductor structures with temperature-dependent sensitivity for unsaturated, 255
- Hydrogen chemisorption
- d.c. conductivity used as sensor for high-temperature, on commercial supported Ni catalysts, 159
- Hysteresis
- capacitive humidity sensor with very fast response time and very low, 291
- Impedance-variation detector
- extremely low-power bipolar integrated, for use in floating-ball flow meter, 193
- Indium
- semiconducting materials based on In₂O₃, gas-sensing characteristics of, depending on composition changes, 285
- Ion-selective field-effect transistor
- flow-through, 297
- Ion-selective sensors
- electrochemical, based on chalcogenide glasses, 275
- ISFET sensor
- use of multi-, fabricated in single substrate, 463
- Lanthanum fluoride
- potentiometric solid-state oxygen sensor using, operative at room temperature, 415
- Magnetorestrictive strain gage
- sensitive, wide frequency range, 323
- Micro gears
- and turbines etched from Si, 341
- Microsensors
- thermal management of integrated, 303
- MIS structure
- Pd-SnO_x, used for oxygen detection, sensing behavior of, 349
- MOS devices
- Pd-gate, for arsine detection, 333
- Moving-strip-illuminated semiconductor panel
- millimeter wave attenuation through and reflection coefficient from, 367
- Multiple regression methods
- and automatic testing equipment, application of, to characterization of 'smart' sensors, 235
- Nickel catalysts
- d.c. conductivity used as sensor for high-temperature H₂ chemisorption on commercial supported, 159
- Noise power
- spectrum density analysis of planar Ag/AgCl electrodes, 185
- Oxygen detection
- Pd-SnO_x MIS structure used for, sensing behavior of, 349
- Oxygen sensor
- potentiometric solid-state, using lanthanum fluoride operative at room temperature, 415
- Palladium
- Pd-gate MOS devices for arsine detection, 333
 - SnO_x MIS structure used for oxygen detection, sensing behavior of, 349
- Photoelastic effect
- fiber-optic catheter-tip sensor based on, 35
- Phthalocyanine
- thin film gas sensors, electrical characteristics of planar, 389

Physical sensors

use of polymer materials as sensitive elements in, 129

Piezoelectric films

for transducers, SOLEF® PVDF bi-axially oriented, 207

Piezoelectric polymer

pressure sensors, 225

Polymer

piezoelectric, pressure sensors, 225

Polymer materials

as sensitive elements in physical and chemical sensors, use of, 129

Polypyrrole electrode

as detector of anionic substances, 455

Pressure sensor(s)

analysis and design of four-terminal Si, at centre of diaphragm, 49

piezoelectric polymer, 225

thick-film fabrication methods for force, assessment of, 57

PVDF

SOLEF®, biaxially oriented piezo- and pyroelectric films for transducers, 207

Pyroelectric films

for transducers, SOLEF® PVDF bi-axially oriented, 207

Radar detection

for automatic control of trains, 313

Radiation meter design

digital, 405

Radiative energy signals

large-area Si sensors for, electro-optical performance of, 23

Reflection coefficient

from moving-strip-illuminated semiconductor panel, millimeter wave attenuation through and, 367

Response time

capacitive humidity sensor with very fast, and very low hysteresis, 291

Scanning electron microscopy

of geometry of V-groove structures, 1

Selective gates

preparation of CHEMFET, by thin silica layer grafting and their behaviour, 245

Selectivity

in semiconductor gas sensors, 425

Semiconducting materials

based on In_2O_3 , gas-sensing characteristics of, depending on composition changes, 285

Semiconductor

gas sensors, selectivity in, 425

p-type thick film gas sensor, 263

thermoelectric devices, fast, 179

thin metal film-oxide-, structures

with temperature-dependent

sensitivity for unsaturated hydrocarbons, 255

Semiconductor panel

moving-strip-illuminated, millimeter

wave attenuation through and

reflection coefficient from, 367

Sensing behavior

of Pd-SnO_x MIS structure used for oxygen detection, 349

Silica layer grafting

preparation of CHEMFET selective gates by thin, and their behaviour, 245

Silicon

micro gears and turbines etched from Si, 341

Silicon sensor(s)

pressure, analysis and design of four-terminal, at centre of diaphragm, 49

for radiative energy signals, electro-optical performance of large-area, 23

Silver

noise power spectrum density analysis of planar Ag/AgCl electrodes, 185

'Smart' sensors

application of multiple regression methods and automatic testing equipment to characterization of, 235

SOLEF®

PVDF biaxially oriented piezo- and pyroelectric films for transducers, 207

Stannic oxide

-based, Sb-doped, thick-film gas sensors, 77

Strain gage

sensitive, wide frequency range magnetorestrictive, 323

Temperature-dependent sensitivity

for unsaturated hydrocarbons, thin metal film-oxide-semiconductor structures with, 255

Temperature transducers

fibre-optic-addressed, using solid-state fluorescent materials, 375

- Thermal fields
 - of zero-method heat flux sensor by electrical analogy, study of, 91
- Thermal management
 - of integrated microsensors, 303
- Thermoelectric devices
 - fast semiconductor, 179
- Thick-film fabrication methods
 - for force (pressure) sensors, assessment of, 57
- Tin
 - Pd-SnO_x MIS structure used for oxygen detection, sensing behavior of, 349
- Tin oxide
 - clean and gas-dosed, fundamental characterization of, 101
- Trains
 - radar detector for automatic control of, 313
- Transducers
 - fibre-optic-addressed temperature, using solid-state fluorescent materials, 375
- SOLEF® PVDF biaxially oriented piezo- and pyroelectric films for, 207
- Transistor(s)
 - chemical selectivity of field-effect, 121
 - flow-through ion-selective field-effect, 297
- Turbines
 - etched from Si, micro gears and, 341
- V-groove structures
 - scanning electron microscopy of geometry of, 1
- Wave attenuation
 - millimeter, through and reflection coefficient from moving-strip-illuminated semiconductor panel, 367
- Zero-method heat flux sensor
 - study of thermal fields of, by electrical analogy, 91

